



DIY Waterproofing and Damp-proofing solutions.

## **Damp Doctor – Grout Sealer**

## **Discussion**

An invisible coating that waterproofs existing grout, as well as preventing algae growth and dirt retention on all tile grout applications. Porous grout in shower cubicles allows water seepage. If no hair line cracking is evident in the grout; the application of *Damp Doctor Grout Sealer*, can often remedy the problem without going to the costly expense of lifting the tiles.

## **Physical Properties**

Colour: Clear

Application: Spray.

Coverage: 4-6m<sup>2</sup>/L

Total Solids: +/- 12.5%

Specific Gravity: +/- 1

Viscosity: <10 Krebbs Units at 25°C

Drying Time: Allow three hours drying time before over coating

Cleaning: Warm soapy water

Flammability: Non - Flammable

## **Application**

During application ensure adequate eye protection (goggles).

Ensure adequate ventilation during and after application.

Damp Doctor Grout Sealer must be used on dry surfaces. Shower should stand for four days before application.

Clean all surface thoroughly. Grouting being treated must be free of all dirt, algae and soap residue.

Repair any loose tiles and fill any fissures or spaces between tiles.

Ensure that all aluminium and glass surfaces are covered before application.

Using a clean rag ensure that any excess Damp Doctor Grout Sealer is wiped away within 10 minutes of application.

Allow 48 hours before exposing the area to water.

DAMP DOCTOR - Grout Sealer page 1